







	EKO SERIJA			OSNOVNA SERIJA		PROFESIONALNA SERIJA
	ADS-NVR4-1E	ADS-NVR8-1E	ADS-NVR32-2E	ADS-NVR16-2	ADS-NVR32-2	ADS-NVR16-8P
						
Št. podprtih kamer	4	8	32	16	32	16
Kompresija	H.264/MJPEG	H.264/MJPEG	H.264/MJPEG	H.264/MJPEG	H.264/MJPEG	H.264/MJPEG
Ločljivost	do 1080P	do 1080P	do 5Mpix	do 5Mpix	do 5Mpix	do 5Mpix
Zmogljivost snemanja	24Mbps	56Mbps	200Mbps	128Mbps	128Mbps	128 Mbps
Alarmni vhod/izhod			4	8	8	16
Relejni izhod			2	3	3	6
Arhiv posnetkov	USB, eSATA, mreža	USB, eSATA, mreža	USB, eSATA, mreža	USB, eSATA, mreža	USB, eSATA, mreža	USB, eSATA, mreža, notranji SATA pekač
Vgrajeni diski	1 SATA do 4 TB	1 SATA do 4 TB	2 SATA do 8 TB	2 SATA do 8 TB	2 SATA do 8 TB	8 SATA do 32 TB (8 HDD ali 6 HDD in 1x CD/DDV-RW)
Število uporabnikov	128	128	128	128	128	128
Zunanji vmesniki	2 x USB 2.0	2 x USB 2.0	2 x USB (USB 3.0, USB 2.0), RS232 1x za tipkovnico in PC, 1x za PTZ kamero	2 x USB 2.0, RS232 1x za tipkovnico in PC, RS485 1x za PTZ kamero	2 x USB 2.0, RS232 1x za tipkovnico in PC, RS485 1x za PTZ kamero	2 x USB 2.0, RS232 1x za tipkovnico in PC, RS485 1x za PTZ kamero
Poraba (brez diskov)	3W	10W	20W	20W	20W	40W
Okolje delovanja	od -10 do +50°C 10% do 90% vlažnost	od -10 do +50°C 10% do 90% vlažnost	od -10 do +55°C 10% do 90% vlažnost	od -10 do +55°C 10% do 90% vlažnost	od -10 do +55°C 10% do 90% vlažnost	od -10 do +55°C 10% do 90% vlažnost
Dimenzije	Kompaktni 1U 260 x 220 x 45 mm	Mini 1U 325 x 255 x 55 mm	1U, 375 x 285 x 55 mm	1U, 375 x 285 x 55 mm	1U, 375 x 285 x 55 mm	2U, 440 x 460 x 89 mm
Teža (brez diskov)	0,8kg	1,25 kg	2,0kg	2,0kg	2,0kg	6,5kg
Cena v EUR brez DDV	116,00	250,00	368,00	559,00	612,00	929,00